



```

ina228_result_t ina228_init( ina228_handle_t*, ina228_attr_t )
ina228_result_t ina228_get_device_info( ina228_handle_t*, ina228_dev_info_t* )
ina228_result_t ina228_set_power_mode( ina228_handle_t*, ina228_power_mode_t )
ina228_result_t ina228_set_sample_rate( ina228_handle_t*, ina228_sample_rate_t )
ina228_result_t ina228_trigger_single_conv( ina228_handle_t* )
ina228_result_t ina228_get_bus_volt( ina228_handle_t*, float* )
ina228_result_t ina228_get_shunt_volt( ina228_handle_t*, float* )
ina228_result_t ina228_get_bus_current_amp( ina228_handle_t*, float* )
ina228_result_t ina228_get_die_temp_degC( ina228_handle_t*, float* )
ina228_result_t ina228_get_power_watt( ina228_handle_t*, float* )
ina228_result_t ina228_get_energy_joule( ina228_handle_t*, uint64_t* )
ina228_result_t ina228_get_charge_c( ina228_handle_t*, uint64_t* )
ina228_result_t ina228_reset_energy_charge( ina228_handle_t* )
  
```

☆ **DRV_TI_INA228** PUBLIC

✓ Passed

Last analysis: 13 seconds ago • 967 Lines of Code • C

A 0

Security

A 0

Reliability

A 0

Maintainability

A —

Hotspots Reviewed

88.3%

Coverage

0.0%

Duplications

